

# MATERIAL SAFETY DATA SHEET

**MANUFACTURER:**

Spectrum Manufacturing Corp. P.O. Box 2087  
Peoria, AZ 85380

Emergency Phone: 623/977-4556

**SECTION I: PRODUCT IDENTIFICATION**

IDENTITY: Spectrum Grout Stain

**SECTION II: COMPONENTS**

	<u>CAS Req. No</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Acrylic Polymer dispersed in water		Non Hazardous	
Limestone	1317-65-3	5	10 Mg/M3
Titanium Dioxide	13463-67-7	10	10 Mg/M3
2-Butoxy ethanol	000111-76-2	25 PPM	25 PPM skin
Ammonium Hydroxide	1335-21-6	50 PPM	25 PPM

**SECTION III: PHYSICAL PROPERTY INFORMATION**

Boiling Point:

Vapor Pressure (mm Hg): Vapor Density:

Specific Gravity (water-1): Solubility in Water: Evaporation rate Appearance / Odor

212-400°F Greater than 1 Heavier than air 1.1-1.4 Dilutable (BUTYL ACETATE -1): Less than one

Thick white to colored, textured mixture, mild ammonia odor, pH 8-10

**SECTION IV: FIRE AND EXPLOSION HAZARD INFORMATION**

Flash Point Explosion Limits: Extinguishing Media: Unusual Fire and Explosion Hazards:

Special Fire Fighting Procedures

>199F PMCC N/A

Carbon Dioxide. Dry Chemical, Alcohol Foam

Closed containers may explode due to the build-up of pressure when exposed to extreme heat.

Full protective equipment including self-contained breathing apparatus should be used. Water may be used to cool closed containers to prevent pressure buildup.

**SECTION V: REACTIVITY DATA**

STABILITY- Stable

INCOMPATIBILITY- None Known

HARROUS DECOMPOSITION PRODUCTS- By fire: Carbon Dioxide, Carbon Monoxide

HARROUS POLYMERIZATION- Will Not Occur

Date Prepared: April 6, 1998